RENAISSANCE

PATIO DOOR









FEATURES & BENEFITS

DESIGNED FOR STRENGTH, ENERGY EFFICIENCY AND EASE OF USE

GLASS PANELS

- 1. Sealed unit with Low-E glass with argon gas
- 2. Warm-edge spacer
- 3. Galvanized 16 gauge steel reinforcements
- 4. Exclusive featherlite tandem rollers

FRAME

- 5. Solid all PVC rot-free sill
- 6. Interior PVC cladding
- 7. Structural 1 ³/₁₆" thick finger-jointed pine jambs and header available in 140 mm (5 ¹/₂"),168 mm (6 ⁵/₈") or 184 mm (7 ¹/₄") depths
- **8.** One-piece extruded jambs and top tracks with seamless PVC exterior cladding
- 9. Air-tight high-fin weatherstripping

HARDWARE


10. Ergonomic level 40 handles (interior & exterior)

SCREEN

- Smooth gliding reinforced aluminum extruded frame, easy to remove for cleaning or storage
- 12. Fiberglass mesh

SECURITY OPTIONS

- 13. Security bar
- **14.** Footlock



COLOUR OPTIONS



- Available in two standard extruded PVC colours: white #141 and cream white #136.
- Paint your door any colour you desire. Choose from one of our standard colours or a custom colour match.

ENERGY EFFICIENCY

HEAT REFLECTIVE Low-E GLASS WITH ARGON GAS

Reflects heated air in winter to keep you warmer









Please check if your door configuration is Energy Star certified at: www.nrcan.gc.ca

GET MAXIMUM ER WITH LOW-E PLUS

Low-E with Argon Gas



Low-E PLUS with Argon Gas



Interior view

U-Value: 1.65 R-Factor: 3.45



U-Value: 1.48 R-Factor: 3.85

EXCLUSIVE LEVEL 40 HANDLE INCLUDED

One of the safest in North America!





Key lock option

MORTISE HANDLE OPTIONS



Available with one-point or two-point locking mechanisms.

OPTIONS

GRILLS BETWEEN THE GLASS



Georgian 5/8" or 1"



Rectangular 5/8"



Slimline

Available in white or painted.

Available in white, pewter, or brass.

SIMULATED DIVIDED LITES






SDL 7/8" without spacer

SDL 2" with spacer

Available in white or painted.

PATTERNS (custom configurations available)







(custom)


ADDITIONAL OPTIONS

- Keylock
- Bronze or grey tinted glass
- Standard size interior frame extensions 8 1/4", 9 1/4" & 9 3/4"
- Interior frame extensions (max. 13 ³/₄")
- PVC brickmould
- PVC capped wood brickmould 11/2" & 2"
- Anodized aluminum sill extension
- · Extruded clear anodized aluminum sill cladding
- Nailing fin
- · Sidelites, toplites, and shaped toplites









S I Z E S Non standard sizes also available

STANDARD WIDTHS

2 LITE - XO/OX

or •		
4'10"	1483 mm	58 ³/ ₈ "
5'	1505 mm	59 ¹/₄"
6'	1784 mm	70 ¹/₄"
7'	2115 mm	83 ¹/₄"
8'	2391 mm	94 ¹/8"

3 LITE - XOO/XOX/OOX

•	or o	r •
8'	2224 mm	87 ⁹ /16"
9'	2643 mm	104 ¹ /16"
10'	3138 mm	123 ⁹ / ₁₆ "
12'	3553 mm	139 ⁷ /8"

3 LITE - OXO-L/OXO-R

-	·	or		4	
8'	22	259 mr	n	3	38 ¹⁵ / ₁₆ "
9'	26	878 mr	n	10	05 ⁷ / ₁₆ "
10'	31	173 mr	n	12	24 ¹⁵ / ₁₆ "
12'	35	588 mr	n	1-	41 ¹ / ₄ "

4 LITE - OXXO

10'	2948 mm	116 ¹ / ₁₆ "
12'	3507 mm	138 1/16"

STANDARD HEIGHTS

6'	1821 mm	71 11/16"*
6' 8"	2019 mm	79 ¹/₂"
6' 10"	2057 mm	81"
8'	2430 mm	95 ¹¹ / ₁₆ "

*Only 5', 6' and 9' doors are offered at 1821 mm (71 11/16") in height.

The manufacturer reserves the right to change or modify products without prior notice.



GUARANTEES

- 20 years against insulated glass seal failure
- 20 years on PVC
- 10 years on parts
- 10 years against spontaneous glass breakage (interior glass only)

Please note that our guarantees are transferable.



info@standarddoors.com
StandardDoors.com/Renaissance









